

aspell を ispell で使う設定

こんな感じの設定にしている .

```
(setq ispell-program-name
      (if (eq system-type 'windows-nt)
          "c:/Program Files/Aspell/bin/aspell.exe"
          (if (eq system-type 'darwin)
              "/opt/local/bin/aspell"
              "/usr/local/bin/aspell")))
(autoload 'ispell-word "ispell" "Check the spelling of word in buffer." t)
(autoload 'ispell-region "ispell" "Check the spelling of region." t)
(autoload 'ispell-buffer "ispell" "Check the spelling of buffer." t)
(autoload 'ispell-complete-word "ispell" "Look up current word in dictionary and try to complete
it." t)
(autoload 'ispell-change-dictionary "ispell" "Change ispell dictionary." t)
(autoload 'ispell-message "ispell" "Check spelling of mail message or newsx post.")
(defun ispell-tex-buffer-p ()
; (memq major-mode '(plain-tex-mode latex-mode slatex-mode yatex-mode)))
;(setq ispell-enable-tex-parser t)

;; 日本語交じりの文書を扱う
(eval-after-load "ispell"
  '(add-to-list 'ispell-skip-region-alist '("[^\u0000-\u377]+")))

;; latex 文書を扱う
(setq ispell-filter-hook-args '("-w"))
(setq TeX-mode-hook
  (function
    (lambda ()
      (setq ispell-filter-hook "detex"))))
```